

SK12-7,2 12V - 7,2AH

The rechargeable batteries are lead-lead dioxide systems. The dilute sulfuric acid electrolyte is absorbed by separators and plates and thus immobilized. Should the battery be accidentally overcharged producing hydrogen and oxygen, special one-way valves allow the gases to escape thus avoiding excessive pressure build-up. Otherwise, the battery is completely sealed and is, therefore, maintenance-free, leak proof and usable in any position.

• SECURITY •

Battery construction

Component	Positive plate	Negative plate	Container	Cover	Safety Valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Rubber	Copper	Fiberglass	Sulfuric acid



General features

- Absorbent Glass Mat (AGM) technology for efficient gas recombination of up to 99% and freedom from electrolyte maintenance or water adding.
- Not restricted for air transport-complies with IATA/ICAO Special Provision A67.
- UL-recognized component.
- Can be mounted in any orientation.
- Computer designed lead, calcium tin alloy grid for high power density
- Long service life, float or cyclic applications.
- Maintenance-free operation.
- Low self discharge.

Dimensions and weight

Length (mm / inch)151 / 5,94
 Width (mm / inch) 65 / 2,56
 Height (mm / inch)..... 94 / 3,70
 Total Height (mm / inch)100 / 3,94
 Approx Weight (Kg / lbs)2,05 / 4,43

Terminal Type : F1 (4,8MM)

Performance characteristics

NOMINAL VOLTAGE..... 12V

NUMBER OF CELL 6

NOMINAL CAPACITY (25°C)

20 hour rate (0.36A - 10.5V) 7.20Ah

10 hour rate (0.66A - 10.5V) 6.60Ah

5 hour rate (1.20A - 10.2V) 6.00Ah

1 hour rate (4.58A - 9.6V) 4.58Ah

INTERNAL RESISTANCE

Fully Charged battery (25°C) 28 mOhms

SELF-DISCHARGE

3% of capacity declined per month at 20°C (average)

OPERATING TEMPERATURE RANGE

Discharge -20 — 60°C

Charge -10 — 60°C

Storage -20 — 60°C

MAX DISCHARGE CURRENT

77°F (25°C) 105A (5s)

CHARGE METHODS Constant Voltage Charge 77°C (25°C)

Cycle use 14,4 — 14,7V

Maximum charging current 2.10A

Temperature compensation -30mV/°C

Standby use 13,5 — 13,8V

Temperature compensation -20mV/°C

INTERNATIONAL STANDARD REFERENCES

- EN 60896-21
- EN 60896-22
- BS 6290-4
- EN 50272-2
- EUROBAT 3-5 years
- “Standard commercial”


CERTIFIED

- ISO 9001
- ISO 14001
- UL Component

CASE BOX

Available in
 Flame Retardant
 UL94 V0 version

Battery and terminal dimensions



Discharge constant current (Ampere at 77°F 25°C)

TIME	5 min	10 min	15 min	30 min	60 min	3 h	5 h	10 h	20 h
9.60V	26,8	16,9	13,4	7,47	4,58	1,80	1,22	0,67	0,37
9.90V	26,0	16,4	13,1	7,32	4,51	1,79	1,22	0,66	0,37
10.2V	24,9	15,7	12,6	7,10	4,40	1,77	1,21	0,66	0,36
10.5V	23,8	15,1	12,2	6,93	4,31	1,76	1,20	0,66	0,36
10.8V	22,5	14,2	11,5	6,67	4,18	1,71	1,16	0,64	0,36

Discharge constant power (Watts at 77°F 25°C)

TIME	5 min	10 min	15 min	30 min	45 min	60 min	2 h	3 h	5 h
9.6V	299	191	153	85,6	68,40	53,1	29,3	21,4	14,6
9.90V	290	185	149	83,9	68,10	52,3	29,1	21,2	14,5
10.2V	278	177	144	81,4	65,20	50,9	28,9	21,1	14,4
10.5V	266	170	139	79,4	63,40	49,9	28,4	20,9	14,3
10.8V	251	160	131	76,5	61,70	48,4	27,7	20,3	13,9